



MH0601K

With MH0601K you get a high-quality door for cold rooms.

Common to all DAN-doors' hinged doors is that they are made of extremely durable materials and characterised by representing a robustness and reliability beyond the ordinary. The doors are of high quality and have a very long service life, even under extremely demanding conditions.

With our hinged doors, you get flexible solutions that can be adapted to meet the requirements of the environment and application in which the door will be used, including use in sensitive environments, such as cleanrooms and foodstuffs, among others.

MH0601K	HINGED 60 MM 1-LEAF DOOR FOR CHILL
BENEFITS	<ul style="list-style-type: none"> Insulated with 60 mm high-insulating and fire-retardant polyisocyanurate foam. Food approved seals. The frame is insulated with mineral wool. Robust construction with very long service life. Requires no (or minimal) maintenance.
DIMENSIONS	<ul style="list-style-type: none"> Maximum width: 1400 mm. Maximum height: 2500 mm. Solutions exceeding the specified maximum dimensions can be custom made. Contact us to explore the possibilities.
FRAME	<ul style="list-style-type: none"> 1,5 mm stainless steel AISI 304. The frame is always insulated.
DOOR LEAF	<ul style="list-style-type: none"> Easy to clean / high hygiene standard (food safe). 1 mm stainless steel AISI 304. 1 mm galvanized steel. 1 mm white PVC (Food safe). Contact us if you want other surfaces.
HINGES	<ul style="list-style-type: none"> Height and side adjustable hinges in stainless steel with frictionless bushings.
SEALING	<ul style="list-style-type: none"> Made of TPE-rubber or silicone, approved for the food industry Sealing strips are mounted directly in the frame and can be replaced without the use of tools.
HANDLES AND LOCK CASES	<ul style="list-style-type: none"> Fermod 920 without locking or 921 with locking D-handle with stainless steel long plate DD-grip - 1-point-grip, 2-point-grip or 3-point-grip Bow handle and pressure plate M-U 1216 lock case with handle / long plates (latch lock) (565) / Night lock M-U lock case 1241 (9788) M-U 1241 lock case (9788) / cylinder / knob M-U 1216 lock case with handle / long plates (latch lock) (565) M-U 1216 lock case with handle / long keys (no lock) (1498) M-U 1222 lock case with handle / long plates (slam lock) (560) M-U 1216 lock case with handle / long plates (no lock) (1498) / DD panic bar back side M-U 1222 lock case with handle / long plates (slam lock) (560) / DD panic bar back side M-U 1222 lock case with handle / long plates (slam lock) (560) / Night lock M-U lock case 1241 (9788) Contact us if you want a different solution.

MH0601K OPTIONAL EQUIPMENT	HINGED 60 MM 1-LEAF DOOR FOR CHILL
WATER CANOPY	<ul style="list-style-type: none"> ▪ Recommended for exterior doors.
WINDOW	<p>Standard sizes:</p> <ul style="list-style-type: none"> ▪ 150 x 300 mm. ▪ 400 x 600 mm. ▪ 500 x 600 mm.
WINDOW FRAME	<ul style="list-style-type: none"> ▪ Anodised aluminium. ▪ Stainless steel.
GLASS	<ul style="list-style-type: none"> ▪ Minimum 2-layer thermo glass.
DOOR PUMP / DOOR CLOSER	<ul style="list-style-type: none"> ▪ Door pump Geze 4000 with arm. ▪ Geze 5000 with sliding rail. ▪ Automatics -Geze Powerturn with safety lists on front and back. ▪ Contact us if you want a different solution.
KICK PLATES	<p>Material - stainless steel AISI 304.</p> <ul style="list-style-type: none"> ▪ Door width x 300 mm (standard). ▪ Door width x 800 mm (standard).