



MH0621I

With MH0621I you get a high-quality security door with many applications.

MH0621I is made of extremely durable materials and is characterized by representing a robustness and reliability beyond the ordinary. You get here a door is of high quality with a long service life, even under extremely demanding conditions.

The doors can be produced with different finishes, for example stainless steel AISI 304 or acid-proof stainless steel AISI 316, to meet the requirements of different environments, such as food and clean rooms.

MH0621I

## HINGED 62 MM 1-LEAF INDUSTRIAL DOOR (STANDARD)

BENEFITS	<ul style="list-style-type: none"><li>▪ 62 mm insulation with either rockwool or highly insulating and fire-retardant polyisocyanurate foam.</li><li>▪ Choice of RAL colours.</li><li>▪ 1,5 mm reinforced frame.</li><li>▪ Available as a burglar-proof door (RC3) in accordance with EN-1627</li><li>▪ Available with a U value of 1.2 W/m<sup>2</sup> x K.</li><li>▪ None or minimal maintenance required.</li></ul>
DIMENSIONS	<ul style="list-style-type: none"><li>▪ Maximum width: 1415 mm.</li><li>▪ Maximum height: 2932 mm.</li><li>▪ <b>Solutions exceeding the specified maximum dimensions can be custom made. Contact us to explore the possibilities.</b></li></ul>
FRAME	<ul style="list-style-type: none"><li>▪ 1,5 mm stainless steel (AISI 304, grit 220).</li><li>▪ 1,5 mm galvanised, painted in a given RAL colour.</li></ul>
DOOR LEAF	<ul style="list-style-type: none"><li>▪ Easy to clean / high hygiene standard (food safe).</li><li>▪ 1 mm stainless steel AISI 304.</li><li>▪ 1 mm stainless steel AISI 316.</li><li>▪ 1 mm galvanized steel, painted in any RAL colour.</li><li>▪ <b>Contact us if you want other surfaces.</b></li></ul>
HINGES	<ul style="list-style-type: none"><li>▪ Stainless steel.</li></ul>
SEALING	<ul style="list-style-type: none"><li>▪ EPDM-seals.</li></ul>
HANDLES AND LOCK CASES	<ul style="list-style-type: none"><li>▪ As standard delivered with long plates in stainless steel.</li><li>▪ Long plates for lock cylinder in stainless steel.</li><li>▪ L-handles delivered in stainless steel.</li><li>▪ <b>Contact us for further information about handles and lock cases.</b></li></ul>

MH06211 OPTIONAL EQUIPMENT	HINGED 62 MM 1-LEAF INDUSTRIAL DOOR (STANDARD)
WATER CANOPY	<ul style="list-style-type: none"> <li>▪ Recommended for exterior doors.</li> </ul>
WINDOW	<ul style="list-style-type: none"> <li>▪ Max-dimensions for windows depend on door size.</li> </ul>
DOORSTEP	<ul style="list-style-type: none"> <li>▪ Different variants, depending on customer's needs.</li> </ul>
DOOR PUMP / DOOR CLOSER	<ul style="list-style-type: none"> <li>▪ Standard door pump: Dorma TS 83 EN 3-6.</li> </ul>
KICK PLATES	<ul style="list-style-type: none"> <li>▪ Stainless steel AISI 304.</li> <li>▪ Door width x 300 mm (standard).</li> <li>▪ Door width x 500 mm (standard).</li> <li>▪ Door width x 700 mm (standard).</li> <li>▪ Door width x 900 mm (standard).</li> </ul>
INSULATION	<ul style="list-style-type: none"> <li>▪ Alternative to rockwool: PIR. PIR insulation allows for a U-value of 1.2 W/m<sup>2</sup> x K.</li> </ul>
AUTOMATICS	<ul style="list-style-type: none"> <li>▪ Available with complete automatic set including safety sensor.</li> </ul>
VENTILATION GRATE	<ul style="list-style-type: none"> <li>▪ 300 x 100 mm with closing system.</li> <li>▪ 300 x 150 mm with closing system.</li> <li>▪ 400 x 100 mm with closing system.</li> <li>▪ 300 x 150 mm with closing system.</li> </ul>