



MH0622I

With MH0622I you get a high-quality industrial door with many applications.

MH0622I is made of extremely durable materials and is characterized by representing a robustness and reliability beyond the ordinary. You get here a door is of high quality with a long service life, even under extremely demanding conditions.

The doors can be produced with different finishes, for example stainless steel AISI 304 or acid-proof stainless steel AISI 316, to meet the requirements of different environments, such as food and clean rooms.

MH0622I

HINGED 62 MM 2-LEAF INDUSTRIAL DOOR (STANDARD)

BENEFITS	<ul style="list-style-type: none">▪ 62 mm insulation with either rockwool or PIR.▪ Choice of RAL colours.▪ 1,5 mm reinforced frame.▪ Available as a burglar-proof door (RC3) in accordance with EN-1627▪ Available with a U value of 1.2 W/m² x K.▪ None or minimal maintenance required.
DIMENSIONS	<ul style="list-style-type: none">▪ Maximum width: 2480 mm.▪ Maximum height: 2930 mm.▪ Solutions exceeding the specified maximum dimensions can be custom made. Contact us to explore the possibilities.
FRAME	<ul style="list-style-type: none">▪ 1,5 mm stainless steel (AISI 304, grit 220).▪ 1,5 mm galvanised, painted in a given RAL colour.
DOOR LEAF	<ul style="list-style-type: none">▪ Easy to clean / high hygiene standard (food safe).▪ 1 mm stainless steel AISI 304.▪ 1 mm stainless steel AISI 316.▪ 1 mm galvanized steel, painted in any RAL colour.▪ Contact us if you want other surfaces.
HINGES	<ul style="list-style-type: none">▪ Stainless steel.
SEALING	<ul style="list-style-type: none">▪ EPDM-seals.
HANDLES AND LOCK CASES	<ul style="list-style-type: none">▪ As standard delivered with long plates in stainless steel.▪ Long plates for lock cylinder in stainless steel.▪ L-handles delivered in stainless steel.▪ Contact us for further information about handles and lock cases.

MH06221 OPTIONAL EQUIPMENT	HINGED 62 MM 2-LEAF INDUSTRIAL DOOR (STANDARD)
WATER CANOPY	<ul style="list-style-type: none"> ▪ Recommended for exterior doors.
WINDOW	<ul style="list-style-type: none"> ▪ Max-dimensions for windows depend on door size.
DOORSTEP	<ul style="list-style-type: none"> ▪ Different variants, depending on customer's needs.
DOOR PUMP / DOOR CLOSER	<ul style="list-style-type: none"> ▪ Standard door pump: Dorma TS 83 EN 3-6.
KICK PLATES	<ul style="list-style-type: none"> ▪ Stainless steel AISI 304. ▪ Door width x 300 mm (standard). ▪ Door width x 500 mm (standard). ▪ Door width x 700 mm (standard). ▪ Door width x 900 mm (standard).
INSULATION	<ul style="list-style-type: none"> ▪ Alternative to rockwool: PIR. PIR insulation allows for a U-value of 1.2 W/m² x K.
AUTOMATICS	<ul style="list-style-type: none"> ▪ Available with complete automatic set including safety sensor
VENTILATION GRATE	<ul style="list-style-type: none"> ▪ 300 x 100 mm with closing system. ▪ 300 x 150 mm with closing system. ▪ 400 x 100 mm with closing system. ▪ 300 x 150 mm with closing system.