

With MH1002K you get a robust door for your cold room.

It is a hinged door made of extremely durable materials and characterized by representing a robustness and reliability beyond the ordinary. The door is of high quality and has a very long service life, even under extremely demanding conditions.

The cold room door is insulated with CFC-free PIR foam and has seals made of food-grade rubber. The door is available in different configurations to fulfil the requirements for use in demanding environments such as food and cleanrooms.



| MH1002K | HINGED 100 MM 2-LEAF COLD ROOM DOOR |
|------------------------|---|
| BENEFITS | 100 mm insulation with highly insulating and fire retardant ployisocyanurate foam. Food-approved seals on both frame and door leaf The frame is insulated with mineral wool. Robust construction with very long service life. Requires no (or minimal) maintenance. |
| DIMENSIONS | Maximum width: 2800 mm. Maximum height: 2500 mm. Solutions exceeding the specified maximum dimensions can be custom made. Contact us to explore the possibilities. |
| FRAME | 1,5 mm stainless steel AISI 304.The frame is always insulated. |
| DOOR LEAF | Easy to clean / high hygiene standard (food safe). 1 mm stainless steel AISI 304. 1 mm galvanized steel. 1 mm white PVC (Food safe). Contact us if you want other surfaces. |
| HINGES | Height and side adjustable hinges in stainless steel with frictionless bushings. |
| SEALING | Made of TPE-rubber or silicone, approved for the food industry Sealing strips are mounted directly in the frame and can be replaced without the use of tools. |
| ESPAGNOLETTE | 2-leaf doors are supplied with espagnolette |
| HANDLES AND LOCK CASES | Fermod 920 without locking or 921 with locking D-handle with stainless steel long plate DD-grip - 1-point-grip, 2-point-grip or 3-point-grip Bow handle and pressure plate. Contact us if you want a different solution. |

| MH1002K Optional equipment | HINGED 100 MM 2-LEAF COLD ROOM DOOR |
|-------------------------------|--|
| WATER CANOPY | Recommended for exterior doors. |
| WINDOW | Standard sizes: • 150 x 300 mm. • 400 x 600 mm. • 500 x 600 mm. |
| WINDOW FRAME | Anodised aluminium.Stainless steel. |
| GLASS | Minimum 2-layer thermo glass. |
| DOOR PUMP / DOOR CLOSER | Door pump Geze 4000 with arm. Geze 5000 with sliding rail. Automatics -Geze Powerturn with safety lists on front and back. Contact us if you want a different solution. |
| DOORSTEP | Stainless steel. |
| GRIP | Grip for retaining door leaf in open position. |
| KICK PLATES | Material – stainless steel AISI 304. Door width x 300 mm (standard). Door width x 800 mm (standard). |

