



Fire curtain E120

This fire curtain is approved for 120 minutes at 1000 degrees.




The fire curtain is made of 2-layer reinforced glass fabric and is certified according to EN-16034 to stop the spread of flames and smoke between buildings, floors and fire zones.

The curtain has no heat reduction on the opposite side and is suitable for protection between buildings, floors and fire zones without regard to personal or material protection.

The fire curtains are prepared for external ABA/ABDL signals so that they automatically close in the event of a fire.

The system is available both wall-mounted and niche-mounted and has a lightweight construction for easy installation. It requires a minimum of space and can be installed in places with very low installation height, making it suitable for places where height can be a challenge.

The inlet box and guide rails can be painted in RAL colours upon request.

E120	FIRE CURTAIN
BENEFITS	<ul style="list-style-type: none"> ▪ Prevents the spread of fire between buildings, zones or floors ▪ Reliable design with minimal maintenance ▪ Lightweight construction that requires a minimum of space ▪ Available both wall and ceiling mounted
DIMENSIONS	<ul style="list-style-type: none"> ▪ Max. width: Unlimited. ▪ Max height: 7000 mm.
CURTAIN	<ul style="list-style-type: none"> ▪ 2-layer reinforced glass fabric
FIRE RESISTANCE	<ul style="list-style-type: none"> ▪ Fire resistance: 120 minutes
GUIDE RAIL	<ul style="list-style-type: none"> ▪ Galvanized steel. ▪ As standard delivered in steel or in RAL-colours 7035, 9002 or 9010. <div style="display: flex; justify-content: space-around; align-items: center; margin: 10px 0;"> <div style="text-align: center;">  <p>RAL 7035 Light grey</p> </div> <div style="text-align: center;">  <p>RAL 9002 Honey yellow</p> </div> <div style="text-align: center;">  <p>RAL 9010 Pure white</p> </div> </div> <ul style="list-style-type: none"> ▪ Available in other RAL colours (option).
AUTOMATIC	<ul style="list-style-type: none"> ▪ 230 V with built-in battery backup.
ABDL	<ul style="list-style-type: none"> ▪ Prepared for external ABA/ABDL signals, so that they automatically close in case of fire.
CERTIFICATION	<ul style="list-style-type: none"> ▪ CE-certified according to EN 16034