


DATA SHEET MH0601B 60 MIN

Hinged 60 mm 1-leaf BS60 fire door (heavy industry)



A high quality fire door for indoor use, approved for 60 minutes fire.

DAN-door's hinged fire doors for heavy industry are approved according to DS 1052.2. This means that the doors are approved according to Danish Standards and resistant to fire for 60 minutes.

The strong construction of the doors ensures that they can be used in particularly challenging environments, such as dairies and slaughterhouses, and because the doors are insulated with fire batts and fireboard, they contribute to lower energy consumption

DATA SHEET MH0601B

BENEFITS	<ul style="list-style-type: none"> ▪ Insulated with 45 mm fire batts og 15 mm fireboard (drywall). ▪ Minimises energy loss. ▪ Fire sealing strips mounted on both frame and door leaf. ▪ Solid construction with a very long service life. ▪ Requires no (or minimal) maintenance. ▪ Certified according to DS-1052.2
DIMENSIONS	<ul style="list-style-type: none"> ▪ Maximum width: 1100 mm. ▪ Maximum height: 2200 mm.
FRAME	<ul style="list-style-type: none"> ▪ 1 mm stainless steel (AISI 304, grain 220). ▪ Frame type 12 and 13 available as circle polished.
DOOR LEAF	<ul style="list-style-type: none"> ▪ Easy to clean / high hygiene standard (food safe). ▪ 1 mm stainless steel AISI 304. ▪ 1 mm galvanized steel. ▪ 1 mm white PVC (Food safe). ▪ Contact us if you want other surfaces.
DOOR PUMP	<ul style="list-style-type: none"> ▪ Adapted to each door. ▪ Strong construction. ▪ Standard door pump: Geze 4000. ▪ Available with stainless steel sheath and arm.
HINGES	<ul style="list-style-type: none"> ▪ Stainless steel bronze bushes.
CERTIFICATION	<ul style="list-style-type: none"> ▪ The door may only be used for personnel access.
HANDLES AND LOCK CASES	<ul style="list-style-type: none"> ▪ Handles and long plate in stainless steel with bronze bushes. ▪ Lock case with stainless steel post supplied prepared for cylinder. ▪ Supplied as standard with long plate or long plate for locking cylinder. ▪ M-U 1216 lock case w. handles/long plates (without locking)(1498). ▪ M-U 1222 lock case w. handles/long plates (slam lock) (560). ▪ Contact us if you want a different solution.

OPTIONAL EQUIPMENT FOR MH0601B

WATER CANOPY	<ul style="list-style-type: none">▪ Recommended for exterior doors.
FIRE WINDOW WITH RS FRAME	<p>Standard sizes:</p> <ul style="list-style-type: none">▪ 150 x 300 mm.▪ 400 x 600 mm.▪ 500 x 600 mm.▪ In case of window the certification is cancelled
DOORSTEP	<ul style="list-style-type: none">▪ Stainless steel.
KICKPLATES	<p>Material - stainless steel AISI 304.</p> <ul style="list-style-type: none">▪ Door width x 300 mm (standard).▪ Door width x 800 mm (standard).