

# DATA SHEET MH0621B60 60 MIN

Hinged 62 mm 1-leaf EI60 fire door (standard)



## High quality fire door EI60.

The EI60 fire door is tested according to EN 1634-1 and certified according to EN 16034-1.

Here you get a safe, high-quality fire door with a minimum of 60 minutes fire protection for both interior and exterior use. The door can be painted in an optional RAL colour to match your brand and design requirements, and is available with a variety of finishes to make it suitable for use in different environments, including food. The door is insulated with rockwool and plaster and fitted with a heavy duty door pump and EPDM smoke seals.

The fire doors can be supplied safety certified RC3 according to EN-1627.

## DATA SHEET MH0621B60 60 MIN

<b>BENEFITS</b>	<ul style="list-style-type: none"> <li>▪ Available as burglar proof door (RC3) according to EN-1627.</li> <li>▪ Fire sealing strips mounted on the door leaf.</li> <li>▪ EPDM smoke seal mounted on the frame.</li> <li>▪ Solid construction with a very long service life.</li> <li>▪ Requires no (or minimal) maintenance.</li> <li>▪ Certified according to EN-16034-1</li> </ul>
<b>DIMENSIONS</b>	<ul style="list-style-type: none"> <li>▪ Maximum width: 1415 mm.</li> <li>▪ Maximum height: 2932 mm.</li> </ul>
<b>FRAME</b>	<ul style="list-style-type: none"> <li>▪ 1,5 mm stainless steel (AISI 304, grain 220).</li> <li>▪ 1,5 mm galvanized, painted in an optional RAL colour.</li> <li>▪ Equipped with EPDM smoke seals.</li> </ul>
<b>DOOR LEAF</b>	<ul style="list-style-type: none"> <li>▪ Easy to clean / high hygiene standard (food safe).</li> <li>▪ 1 mm stainless steel AISI 304.</li> <li>▪ 1 mm acid-proof stainless steel AISI 316.</li> <li>▪ 1 mm galvanized, painted in an optional RAL colour.</li> <li>▪ <b>Contact us if you want other surfaces.</b></li> </ul>
<b>DOOR PUMP</b>	<ul style="list-style-type: none"> <li>▪ Adapted to each door.</li> <li>▪ Strong construction.</li> <li>▪ Standard door pump: Dorma TS 83 EN 3-6.</li> </ul>
<b>HINGES</b>	<ul style="list-style-type: none"> <li>▪ Stainless steel.</li> </ul>
<b>CERTIFICATION</b>	<ul style="list-style-type: none"> <li>▪ EN 16034-1.</li> </ul>
<b>HANDLES AND LOCK CASES</b>	<ul style="list-style-type: none"> <li>▪ Supplied as standard with stainless steel long plates.</li> <li>▪ L-handles for lock cylinder are supplied in stainless steel.</li> <li>▪ L-handles are supplied in stainless steel.</li> <li>▪ <b>Contact us if you want a different solution.</b></li> </ul>

## OPTIONAL EQUIPMENT FOR MH0621B60

WATER CANOPY	<ul style="list-style-type: none"> <li>Recommended for exterior doors.</li> </ul>
ENLARGED WINDOW WITH RS FRAME	<ul style="list-style-type: none"> <li>Max. 500 x 1800 mm pyrobel 25-EI60.</li> <li>The doors are also available with round windows. Contact us for details.</li> </ul>
KICKPLATES	
DOORSTEP	<ul style="list-style-type: none"> <li>Different variants.</li> </ul>
KICKPLATES	<p>Material - stainless steel AISI 304.</p> <ul style="list-style-type: none"> <li>Door width x 300 mm (standard).</li> <li>Door width x 500 mm (standard).</li> </ul>
AUTOMATICS	<ul style="list-style-type: none"> <li>Door width x 700 mm (standard).</li> <li>Door width x 900 mm (standard).</li> </ul>
AUTOMATICS	<ul style="list-style-type: none"> <li>Available with complete automatic kit, including safety cord.</li> </ul>