



MH0621RC3

High-quality security door

This door provides you with certified burglary protection in a robust and reliable solution. It has been tested and approved as an RC3 security door in accordance with EN 1627, which means it can withstand burglary attempts using common hand tools for an extended period of time. This makes it an effective barrier against unauthorized access and vandalism.

An RC3 security door is particularly attractive for buildings where a high level of security is required. Examples include office buildings, schools, public facilities, warehouses, production areas, residential buildings, or other locations where a strong and aesthetically adaptable security solution is desired.

The door can be supplied with different surface finishes and in any RAL colour of your choice, making it easy to adapt to both the functional requirements and the architectural framework of your project.

MH0621RC3	HINGED 62 MM 1-LEAF SECURITY DOOR — RC3
BENEFITS	 Burglar-resistant door (RC3), certified according to EN 1627. Sealing strips mounted on the door leaf. EPDM smoke seal mounted on the frame. Solid construction with a very long service life. Requires no (or minmal) maintenance.
DIMENSIONS	Maximum width: 1485 mm.Maximum height: 2700 mm.
FRAME	 1,5 mm stainless steel (AISI 304, grain 220). 1,5 mm galvanized, painted in an optional RAL colour. Equipped with EPDM smoke seals.
DOOR LEAF	 62 mm Insulation: rockwool and gypsum Easy to clean / high hygiene standard (food safe). 1 mm stainless steel AISI 304. 1 mm acid-proof stainless steel AISI 316. 1 mm galvanized, painted in an optional RAL colour. Contact us if you want other surfaces.
HINGES	Stainless steel.
SECURITY CERTIFICATION	• EN 1627.
HANDLES AND LOCK CASES	 Supplied as standard with stainless steel long plates. Long plates for lock cylinder are supplied in stainless steel. L-handles are supplied in stainless steel. Contact us if you want a different solution.



MH0621RC3 OPTIONAL EQUIPMENT	HINGED 62 MM 1-LEAF SECURITY DOOR — RC3
WATER CANOPY	Recommended for exterior doors.
WINDOW	The max.dimensions for windows depend on the door size.
DOORSTEP	Different variants.
DOOR CLOSER	 Adapted to each door. Strong construction. Standard door closer: Dorma TS 83 EN 3-6.
KICKPLATES	 Material - stainless steel AISI 304. Door width x 300 mm (standard). Door width x 500 mm (standard). Door width x 700 mm (standard). Door width x 900 mm (standard).
AUTOMATICS	Available with complete automatic kit, including safety cord.

