



MH1002RC4T1

High-quality security door

This door provides you with certified burglary protection in a robust and reliable solution. It has been tested and approved as an RC4 security door in accordance with EN 1627, which means it can withstand advanced burglary attempts using heavy-duty tools over an extended period of time. This makes it a highly effective barrier against unauthorized access and organized break-in attempts.

An RC4 security door is particularly attractive for buildings where the highest security requirements apply. Examples include data centres, critical infrastructure facilities, laboratories, energy supply facilities, server rooms, high-value storage areas, or other locations where value protection and strict access control are crucial.

The door is supplied with a transom panel that can be opened when needed, providing great flexibility in terms of opening. It can of course also be delivered with different surface finishes and in any RAL colour of your choice, ensuring that it meets your requirements for both functionality and architectural design.



MH1002RC4T1	HINGED 100 MM 2-LEAF SECURITY DOOR WITH TOP PANEL — RC4
BENEFITS	 Burglar-resistant door (RC4), certified according to EN 1627. Available in very large sizes. Sealing strips mounted on the door leaf. EPDM smoke seal mounted on the frame. Solid construction with a very long service life. Requires no (or minmal) maintenance.
DIMENSIONS	Maximum width: 2120 mm.Maximum height: 2990 mm.
FRAME	 1,5 mm stainless steel (AISI 304, grain 220). 1,5 mm galvanized, painted in an optional RAL colour. Equipped with EPDM smoke seals.
DOOR LEAF	 Easy to clean / high hygiene standard (food safe). 1 mm stainless steel AISI 304. 1 mm acid-proof stainless steel AISI 316. 1 mm galvanized, painted in an optional RAL colour. Contact us if you want other surfaces.
HINGES	Stainless steel.
SECURITY CERTIFICATION	- EN 1627.
HANDLES AND LOCK CASES	 Supplied as standard with stainless steel long plates. Long plates for lock cylinder are supplied in stainless steel. L-handles are supplied in stainless steel. Contact us if you want a different solution.



MH1002RC4T1 OPTIONAL EQUIPMENT	HINGED 100 MM 2-LEAF SECURITY DOOR WITH TOP PANEL — RC4
WATER CANOPY	Recommended for exterior doors.
DOORSTEP	Different variants.
DOOR CLOSER	 Adapted to each door. Strong construction. Standard door closer: Dorma TS 83 EN 3-6.
KICKPLATES	 Material - stainless steel AISI 304. Door width x 300 mm (standard). Door width x 500 mm (standard). Door width x 700 mm (standard). Door width x 900 mm (standard).
AUTOMATICS	Available with complete automatic kit, including safety cord.

