

DATA SHEET MS1001K

Manual 100 mm 1-leaf door for cold room



MS1001K is a robust and reliable manual sliding door for refrigeration.

This sliding door is insulated with 100 mm fire-retardant polyisocyanurate foam, which makes it ideal for use in cold rooms where extra high demands are placed on food quality, temperature safety and hygiene. It is a robust door that has a very long lifetime and meets the most stringent requirements in the food industry.

This port is tailored for companies that:

- ✓ Need excellent insulation of their cold room
- ✓ Work consistently with energy savings and sustainable operation
- ✓ Prioritise high quality and a long service life
- ✓ Want a door that requires no maintenance

DATA SHEET MS1001K

BENEFITS	<ul style="list-style-type: none"> ▪ 100 mm high insulating foam ensures excellent energy saving properties. ▪ Food-approved seals on both frame and door leaf. ▪ Complies with the strictest requirements in the food industry. ▪ Robust construction with very long service life. ▪ Requires no (or minimal) maintenance.
DIMENSIONS	<ul style="list-style-type: none"> ▪ Max. width: 3200 mm. ▪ Max height: 3600 mm. <p>Solutions exceeding the specified maximum dimensions can be custom made. Please contact us to explore the possibilities.</p>
FRAME	<ul style="list-style-type: none"> ▪ 1,5 mm stainless steel. ▪ The frame is always insulated.
WHEELS	<ul style="list-style-type: none"> ▪ Wheels in POM or Stainless steel (64 mm or 80 mm). ▪ Brackets, stud bolt, washer and nuts in Stainless steel.
DOOR LEAF	<ul style="list-style-type: none"> ▪ 1 mm stainless steel AISI 304. ▪ 1mm white PVC (Food safe). <p>Contact us if you want other surfaces.</p>
RECESS	<ul style="list-style-type: none"> ▪ Sliding rail is supplied with recess blocks to ensure hermetic closing towards frame and floor.
GASKETS	<ul style="list-style-type: none"> ▪ Quality gaskets approved for use in the food industry. ▪ Fitted into anodized aluminum profiles.
HANDLES	<ul style="list-style-type: none"> ▪ Front side - solid DAN-doors stainless steel handle fitted, on the edge of the door leaf. ▪ Back side - stainless torque handle.
BOTTOM GUIDES	<ul style="list-style-type: none"> ▪ Manufactured in salt water resistant anodized aluminum. ▪ The bottom guides are supplied with solid nylon bushes.

OPTIONAL EQUIPMENT FOR MS1001K

LOCKS	<ul style="list-style-type: none"> ▪ Cylinder lock with emergency opening made of black PEHD plastic and stainless steel. ▪ Heating elements in locks for frost (can be locked from front or back side). ▪ Padlock fittings with or without emergency opening made of black PEHD plastic (can be locked from front or back side).
WINDOW	<p>Standard sizes:</p> <ul style="list-style-type: none"> ▪ 150 x 300 mm. ▪ 400 x 600 mm ▪ 500 x 600 mm
WINDOW FRAME	<ul style="list-style-type: none"> ▪ Anodised aluminium ▪ Stainless steel.
GLASS	<ul style="list-style-type: none"> ▪ Minimum 2-layer thermo glass.
SLIDING RAIL COVER	<ul style="list-style-type: none"> ▪ Normally supplied in the same material as the door leaf.
EMERGENCY HATCH/DOOR	<ul style="list-style-type: none"> ▪ Emergency hatch in 600 x 1000 mm. ▪ Door in 800 x 1800 mm <p>Please contact DAN-doors regarding handles and locks.</p>
KICK PLATES	<p>Material - Stainless steel AISI 304</p> <ul style="list-style-type: none"> ▪ Door width x 300 mm (standard) ▪ Door width x 800 mm (standard).
AUTOMATICS	<p>Tooth belt automatic system (1 x 230 V / 50 Hz)</p> <ul style="list-style-type: none"> ▪ Push buttins ▪ Pull cords w. switch ▪ Radar ▪ Remote controls and receivers