



Fire shutter BLA EI₂60

This fire shutter is approved for 60 minutes.

It is designed to be connected to the fire alarm system so that the fire shutter automatically shuts down and protects against further fire development.

The fire shutter can be used daily as a safety roller shutter and is suitable for various applications in commercial and industrial buildings: shopping centres, warehouses, factories, car parks, etc.

The guide rails and curtain can be painted in different colours.

FIRE SHUTTER BLA EI₂60

FIRE SHUTTER EI₂60

BENEFITS	<ul style="list-style-type: none">▪ Can be used daily as a normal security closure.▪ Prevents the spread of fire between buildings, zones or floors.▪ Optimizes evacuation conditions.▪ Reliable construction with minimal maintenance.▪ Fire resistance on both sides.▪ No need for water/sprinkler.▪ Certified according to EN 16034 and EN 13241.▪ Excellent alternative to sliding fire doors.▪ Can be installed as an external closure (wind resistance class 2).
DIMENSIONS	<ul style="list-style-type: none">▪ Max. width: 8000 mm.▪ Max height: 6000 mm.
BLINDS MAT	<ul style="list-style-type: none">▪ Slat height: 110 mm.▪ Slat thickness: 50 mm.
FIRE RESISTANCE	<ul style="list-style-type: none">▪ 60 minutes.
GUIDE RAIL	<ul style="list-style-type: none">▪ Galvanised steel.▪ Black sealing strip.
AUTOMATIC	<ul style="list-style-type: none">▪ 3 x 400 V motor and battery backup.
CERTIFICATION	<ul style="list-style-type: none">▪ CE-certified according to EN 16034 and EN 13241